

16

GREAT REASONS

TO RELY ON TITANIUM FOR YOUR NEXT ROOFING PROJECT.

TITANIUM®

SYNTHETIC ROOFING UNDERLAYMENT

Roofers

rely on it.™

1. Titanium® is the #1 selling brand and is backed by one the largest field support teams in the industry
2. All Titanium UDL products have our patented Sure-Foot® slip-resistant nodular walking surface and backside slip resistant resin technology for advanced underlayment to roof deck slip resistance
3. Titanium lays flat and will not absorb water and wrinkle like felt, nor will it dry out, leach oils in the heat, or become stiff, and difficult to roll or crack in the cold
4. Exceptional durability and strength allow all UDL underlayments, if installed correctly, to be left exposed without suffering from blow-offs and tears like oil saturated felts - no need for tarps!
5. Faster installs - UDL products are lighter, wider, easier to handle, and longer than felt, which means less laps and seams per job - saving you up to 30% on labor time, energy and money
6. 1 roll of UDL is equivalent in gross sq ft to 4.85 rolls of 30 lb felt
7. Cool gray surface reduces heat during install and does not expand or contract
8. Titanium products are ICC, Intertek & Miami-Dade code approved and exceed ASTM D226 & D4869 standards
9. UDL's and PSU are part of an ASTM E-108 class A fire system and meet Class 4 Hail Rating
10. All Titanium products now come with a †Lifetime Limited Warranty
11. Synthetic underlayment is unaffected by water and inert to mold
12. Excellent poly foam adhesion properties - Titanium products are Polyset® approved
13. Installation instructions are in 3 languages (English, Spanish & French)
14. All UDL products are available in Dual-logo. Turn your next roofing job into a massive billboard!
15. PSU30 self-adhesive ice dam protection underlayment is designed for high & low temperature performance
16. PSU30 - Incorporates a unique lap seal system which forms a watertight asphalt to asphalt bond at overlapping seams

PRODUCT FEATURES	UDL25	UDL30	UDL50	PSU30
Material Thickness	15 mils	25 mils	30 mils	45 mils
Weight Per Roll/Rolls Per Pallet	25 lbs / 56	40 lbs / 30	49 lbs / 25	48 lbs / 25
X times stronger than 30 lb felt	14 times stronger	20 times stronger	25 times stronger	N.A.
X lighter than 30 lb felt	11 times lighter	6 times lighter	5 times lighter	N.A.
UV exposure/Days uncovered	6 months	6 months	6 months	6 months
Gross Roll size / Dimensions	10 Sq / 48" x 250'	10 Sq / 48" x 250'	10 Sq / 48" x 250'	2 Sq / 36" x 72'
Slip resistant walking surface	*Sure-Foot®	*Sure-Foot®	*Sure-Foot®	*Sure-Foot®
Cool gray surface	✓	✓	✓	✓
Unaffected by mold	✓	✓	✓	✓
Custom Dual-Logo printing	✓	✓	✓	
Contribute to LEED® pts	✓	✓	✓	
Recyclable	✓	✓	✓	
For use under	Metal, Shake & Shingle	Metal, Slate, Shake, Shingle & Tile	All primary roofing types	All primary roofing types

*Sure-Foot® is a patented slip-resistant nodular walking surface that provides excellent walkability, even when wet.

†See www.InterWrap.com/LifetimeWarranty for complete coverage and restrictions

Over
25 Million
Squares Sold!

TITANIUM®

SYNTHETIC ROOFING UNDERLAYMENT

COMPARE THE DIFFERENCE!

TITANIUM® UDL VS. ROOFING FELT

ROOFING FACTFINDER

	TITANIUM®	FELT
Lifetime Warranty	✓	✗
Inert to mold growth	✓	✗
High resistance to wind	✓	✗
Does not absorb water & wrinkle	✓	✗
Does not dry out and degrade	✓	✗
Does not leach oil	✓	✗
*Class A fire rating	✓	✗
Meets class 4 hail rating	✓	✗
Supports building green	✓	✗

TECHNICAL COMPARISON

DESCRIPTION	UDL30	15 lb FELT	30 lb FELT
Width	48"	36"	36"
Length per roll	250 ft.	144 ft.	72 ft.
Rolls per 1000 sq. ft.	1 roll	3 rolls	5 rolls
Rolls required per 5000 square ft. roof	5 rolls (200 lbs)	12 rolls (420 lbs)	24 rolls (744 lbs)

NOTES

D226 Felt weights and measures are nominal and may vary from manufacturer to manufacturer.

- Over 1,000,000 homes are protected under Titanium
- Titanium does not break down, dry out and degrade like felt
- Synthetic material avoids potential chemical incompatibility between primary roofing and petroleum impregnated felt
- Storm protection - stronger waterproof membrane acts as a secondary layer of protection
- Reduces liability - safer slip resistant walking surface

*ASTM D226 UL marked felts are the only felts with a class A rating. *See InterWrap.com/LifetimeWarranty for complete coverage and restrictions



weaving a better world™

Titanium products are ICC, Intertek & Miami-Dade code approved and exceed ASTM D226 standards

Ask for Titanium at your roofing distributor or lumber dealer.

InterWrap.com/Titanium
Toll Free: 888 713 7663