

TITANIUM™ Roofing Products Information

TITANIUM™ PSU-30 PEEL & STICK Synthetic Roofing Underlayment



Features & Benefits

FOR USE UNDER ALL: • METAL • TILE • SLATE • SHAKE • SHINGLE

- **NEW!** TITANIUM PSU-30 is now an approved POLYFOAM underlayment for use with POLYSET® foam systems!
- The only modified rubberized asphalt PEEL & STICK with a tough and rugged surface
- Industry only Self Sealing Lap System!
- Now with a 30 Year Limited Warranty
- All temperature performance (40° F to 240° F)
- Patented SURE-FOOT™ slip resistant technology for easy steep slope walk-ability
- Synthetic construction inert to mold growth
- Cool light gray surface, doesn't expand or contract
- 3 Month UV exposure



CLASS A ASTM E-108
CAN/CSA A220.1



InterWrap Inc.

Customer Service

Toll Free: 1-888-713-7663

Fax: 1-604-820-5420

E-mail: info@interwrap.com

32923 Mission Way,

Mission, BC Canada, V2V 6E4

InterWrap, The InterWrap logo and TITANIUM are trademarks of InterWrap Inc. in Canada, The United States and other countries, used under license by InterWrap Corp. in the United States and IBCO SRL worldwide. © 2009

TITANIUM™ PSU-30 is the only modified rubberized asphalt PEEL & STICK with a tough, rugged surface AND the Roofing Industries only SELF-SEALING lap system!

TITANIUM™ PSU-30 is an advanced, uniquely gray, synthetic polymer surfaced self-adhered membrane roofing underlayment for sloped roofs subject to the effects of ice damming and wind driven rain. With Micron Dispersion Polymer (MDP) technology, TITANIUM™ PSU-30 rubberized asphalt delivers a unique combination of both high temperature (240°F / 115°C) flow resistance, and low temperature (40°F / 4.4 °C) deck adhesion "ALL TEMP" performance. This is combined with a revolutionary patented slip resistant SURE-FOOT™ nodular walking surface technology, a super tough, durable, and reflective gray synthetic polymer surface, a 3 month UV exposure rating, and an industry leading 30 year limited warranty...all in ONE product!

Unlike other brands with multiple roll offerings for different roof types, a single TITANIUM™ PSU-30 product can be used under all types of roofing materials such as metal, tile, shake, slate and composition shingles. Used in conjunction with TITANIUM™ UDL-30 synthetic roofing underlayment, these 2 products (UDL-30 & PSU-30) offer the sloped roofing category a unique combination of safety, security and simplicity!

TITANIUM™ PSU-30, with its unique construction, provides superior performance in use. Its unique rubberized asphalt formulation helps to prevent buckles or wrinkles when exposed to temperature and moisture variations on a roof, and furthermore, it provides for outstanding flexibility for installation ease. TITANIUM™ PSU-30 is also granular surface free. Loose granules can become a safety hazard, score the underneath of metal roofing systems, and track underneath footing causing damage to metal roofing systems. Granular surfaced membranes also deliver inferior seam overlap strengths and integrity; a critical issue for ice damming and wind driven rain protection.

TITANIUM™ PSU-30 possesses an advanced engineered synthetic polymer surface, which forms an indestructible bond at overlapping seams, delivering superior protection. In addition, the revolutionary patented SURE-FOOT™ nodular walking surface provides for increased worker safety in wet and dusty conditions. And TITANIUM™ PSU-30 delivers all this technology in one product! Reduce inventory of multiple roll types and sizes... TITANIUM™ PSU-30 is all you need.

If superior protection and safety performance wasn't enough, TITANIUM™ PSU-30 can also be left exposed for up to 3 months! Increase your job schedule flexibility and efficiency! And similar to TITANIUM™ UDL-30, TITANIUM™ PSU-30 possesses a category leading 30 year limited warranty. Give your valuable primary roofing the insurance it really needs. Specify TITANIUM™ PSU-30 !

TITANIUM™
SYNTHETIC ROOFING UNDERLAYMENT

Roofers rely on it.