

TITANIUM™ Roofing Products Information

TITANIUM™ PSU-30 PEEL & STICK Synthetic Roofing Underlayment



Code Listings

- ICC-ES ESR-1306
- Class A ASTM E-108 Intertek Report # 3133961 - 01
- CAN/CSA A220.1 - M91 Intertek Report # 3126617COQ-009
- Florida Building Code (FBC) FL6203
- MIAMI-DADE [PENDING]

Technical Data

TEST & PROPERTIES	STANDARD	TITANIUM™ PSU-30 TYPICAL VALUE
Color		Gray
Surface		Synthetic Polymer - Patented SURE-FOOT™ slip resistant
Release Liner		Silicone Treated, Poly Split Release
Weight per square		24 lbs / (10.8 kg)
Minimum Thickness	ASTM D5147	45 Mil (1.1 mm)
Tensile	ASTM D1970	MD 100 lbs/in/ (17.5 kN/m) CD 80 lbs/in (14 kN/m)
Thermal Stability	ASTM D1970	240° F (115° C) Pass
Low Temp Flexibility	ICC AC 48	Pass
Tear Resistance	ASTM D1970	MD 140/ CD 100 lbf (622/445 N)
Adhesion to Plywood	ASTM D903	4 lb/in (700 N/m)
Self Seal Ability	ASTM D1970	Pass
Temperature Range		240° F (115° C) to 40° F (4.4° C)

LENGTH PER ROLL:	72' / 22 m
WIDTH PER ROLL:	36" / 91.4 cm
WEIGHT PER ROLL:	48 lbs / 22 kg
NET ROLL SIZE:	2 sq / 20 m ²
ROLLS PER PALLET:	25
PALLET WEIGHT:	1300 lbs / 590 kg

Test data is based on an average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values \pm 10%. Dry tested conditions: in water, #30 felt will absorb +30% water and lose +50% strength when wet. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures. Values are typical data and not limiting specifications. All values \pm 10%



InterWrap Inc.
Customer Service
Toll Free: 1-888-713-7663

Fax: 1-604-820-5420

E-mail: info@interwrap.com

32923 Mission Way,

Mission, BC Canada, V2V 6E4

InterWrap, The InterWrap logo and TITANIUM are trademarks of InterWrap Inc. in Canada, The United States and other countries, used under license by InterWrap Corp. in the United States and IBCO SRL worldwide. © 2009

TITANIUM™
SYNTHETIC ROOFING UNDERLAYMENT

Roofers rely on it.