

Protect your valuable investments



RhinoWrap™ 95

RhinoWrap™ is a high strength coated woven polyethylene fabric that provides industry leading protection for your valuable investments. RhinoWrap is ideal for both indoor and outdoor applications such as: Truck tarps, agricultural tarps, temporary shelters, poultry curtains and roofs, ground covers, freight covers, machine covers, liners for drums, floor underlays, firewood covers, packaging, bags and much more.

- Coated woven scrim design is Up to 3X stronger than blown film XF products.
- Comparison statistics available – provided by independent Intertek labs using North American ASTM testing standards.
- Superior 2-3 year service life expectancy – competitor blown film XF tarpaulins are only 6 months to a year.
- UV Stabilized fabric – UV additives in all layers – backed by unique industry leading 1 year UV guarantee.
- High quality brand reputation - manufactured by a leading Canadian multinational corporation and global exporter with 29 Years of proven product quality.
- Resilient – Impact and puncture resistant, product holds its shape while still remaining flexible with up to 22% stretch.
- Unaffected by most cleaning chemicals and surfactants, inert to mold or bacteria
- Internal woven core stops tears from propagating.
- 100% waterproof with excellent gas barrier properties.
- Manufactured to IS: 7903:2011 under ISO 8000 product quality and control standards with <10% weight variance.

ENGINEERED LLDPE/LDPE COATINGS

For flexibility, chemical resistance and protection against UV, ozone and oxidation.

HDPE HIGH STRENGTH WOVEN CORE

For superior dimensional stability and strength.



InterWrap.com

Toll Free: 800 567 9727 | Tel: 778 945 2888 | Email: info@interwrap.com

RW-95-R1-19May2016



weaving a better world™



RhinoWrap™ 95



RhinoWrap 95 Applications:

RhinoWrap™ is a high strength coated woven polyethylene fabric that provides industry leading protection for your valuable investments. RhinoWrap is ideal for both indoor and outdoor applications such as: Truck tarps, agricultural tarps, temporary shelters, poultry curtains and roofs, ground covers, freight covers, machine covers, liners for drums, floor underlays, firewood covers, packaging, bags and much more.

Available Sizes & Color

- Up to 144" wide rolls (3.66m)
- 9 mil (0.23mm) thickness
- Blue/Blue & Yellow/Yellow

PROPERTY	TEST/METHOD	RHINOWRAP 95 TYPICAL VALUE
Color		Blue/Blue & Yellow/Yellow
Available Widths		Up to 144" (3.66m)
Coatings		Two sides LDPE
Weight	ASTM D5261	2.6 oz/yd ² (88 gsm)
Nominal Thickness	ASTM D1777	9 mil (0.23mm)
Tensile Strength	ASTM D751	MD 40 lb (18.1 kg) CD 40 lb (18.1 kg) 20% Elongation
Trapezoidal Tear	ASTM D4533	MD 16 lb (7.2 kg) CD 16 lb (7.2 kg) 20% Elongation
Mullen Burst	ASTM D751	120 Psi (827 kPa)
Accel. UV Weathering	ASTM G154	>90% 2000 hrs [†]

All tests are ± 10%. [†]QUV A-340 lamps 8 hrs UV @ 60° C, 4 hrs condensation @ 40°.
The test data is based on an average taken over several production runs and should not be considered or interpreted as minimum or maximum values.
Values are typical data and not limiting specifications.