


RhinoRoof® U20

Synthetic Roofing Underlayment


U20 Technical Data



U20 ROLL & PALLET SPECIFICATIONS	
LENGTH PER ROLL:	286' / 87 m
WIDTH PER ROLL:	42" / 1.1 m
WEIGHT PER ROLL:	23.5 lbs / 10.6 kg
ROLL SIZE:	10 sq / 93 m ²
ROLLS PER PALLET:	67
PALLET WEIGHT:	1,626 lbs / 738 kg

TEST & ASTM STANDARD	RHINOROOF U20 TYPICAL VALUE	#30 FELT TYPICAL VALUE
Class A Fire E108	Pass	N/A
Permeability E96	.05 perms	1.75 perms
Water Transmission D4869	Pass	Pass
Tear Strength D4533	MD 33 lbs (15 kg) CD 24 lbs (11 kg)	MD 4 lbs (1.8 kg) CD 2 lbs (0.9 kg)
Tensile Strength D751	MD 88 lbs (40 kg) CD 70 lbs (32 kg)	MD 70 lbs (32 kg) CD 38 lbs (17 kg)
Burst Strength D751	158 psi (1089 kPa)	62 psi (430 kPa)
Elongation D751	MD 20% CD 20%	MD 2% CD 2%
Weight per Square D5261	2.25 lbs (1.02 kg)	27.5 lbs (12.5 kg)
Nominal Thickness D1777	7 mils (0.18 mm)	60 mils (1.5 mm)
Service Temperature Range	-40 °F to 240 °F (-40 °C to 115 °C)	

U20 Building Codes



- Meets and exceeds ASTM D226 Types I & II and D4869 Types II & IV
- Miami-Dade County approved
- Florida Building Code approved
- Texas Department of Insurance listed
- Class A Fire - ASTM E108
- CAN/CSA A123.3
- CCRR-1015



weaving a better word™

InterWrap® Roofing Products Division

Charleston, SC • Vancouver, BC • Mission, BC • Montréal, QC
Web: www.InterWrap.com/roofing | E-mail: info@interwrap.com
Toll Free: 888 713 7663 | Tel: 778 945 2888

