

**TITANIUM® UDL25**  
VALUE GRADE



**TITANIUM® UDL30**  
PROFESSIONAL GRADE



**TITANIUM® UDL50**  
ELITE GRADE



**TITANIUM® PSU-30**  
ICE DAMMING PROTECTION



# TITANIUM®

**SYNTHETIC ROOFING UNDERLAYMENT**

**TITANIUM®**

**LIFETIME\***

**LIMITED  
WARRANTY**

InterWrap's Titanium® Synthetic Roofing Underlayments are the ideal choice for all types of roofing applications. With Titanium you will benefit from over twelve years of research and development that has resulted in the most advanced synthetic underlayments in the industry.

- Rest assured knowing your underlayment is covered by an industry leading Lifetime\* Warranty
- Titanium high strength coated woven material provides a premium secondary layer of protection against wind driven rain, blow-offs, hail storms and other violent acts of Mother Nature
- Proven performance – over 1, 000,000 homes are protected by Titanium underlayments
- Increase the true life of your roof – Titanium does not break down, dry out and degrade like felt
- Titanium UDL's are 100% recyclable
- Reduce your liability - ensure workers on your roof have the best possible walking surface - safer
- Wider and longer rolls offer fewer horizontal and vertical seams on your roof which reduces the number of potential leaks
- Up to 25 times stronger than felt paper!
- Titanium products can be left exposed to dry-in your home for up to 6 months. This allows for more flexibility in scheduling your primary roofing install



weaving a better world™

For more information call toll free:

**888-713-7663**

Email: [info@interwrap.com](mailto:info@interwrap.com)

Web: [InterWrap.com/Titanium](http://InterWrap.com/Titanium)

**Roofers**  
**rely on it.™**

\*See [InterWrap.com/LifetimeWarranty](http://InterWrap.com/LifetimeWarranty) for complete coverage and restrictions.

PHOTO: 15/MAY/2015

Storm protection by

# TITANIUM®

SYNTHETIC ROOFING UNDERLAYMENT

Roofers

rely on it.™

## TITANIUM® UDL VS. ROOFING FELT

ROOFING  
FACTFINDER

	TITANIUM®	FELT
Lifetime* Warranty	✓	✗
Inert to mold growth	✓	✗
High resistance to wind	✓	✗
Does not absorb water & wrinkle	✓	✗
Does not dry out and degrade	✓	✗
Does not leach oil	✓	✗
*Class A fire rating	✓	✗
Meets class 4 hail rating	✓	✗
Supports building green	✓	✗

## TECHNICAL COMPARISON

DESCRIPTION	UDL30	15 lb FELT	30 lb FELT
Width	48"	36"	36"
Length per roll	250 ft.	144 ft.	72 ft.
Rolls per 1000 sq. ft.	1 roll	3 rolls	5 rolls
Rolls required per 5000 square ft. roof	5 rolls (200 lbs)	12 rolls (420 lbs)	24 rolls (744 lbs)

## NOTES

D226 Felt weights and measures are nominal and may vary from manufacturer to manufacturer.

- Over 1,000,000 homes are protected under Titanium
- Titanium does not break down, dry out and degrade like felt
- Synthetic material avoids potential chemical incompatibility between primary roofing and petroleum impregnated felt
- Storm protection - stronger waterproof membrane acts as a secondary layer of protection
- Reduces liability - safer slip resistant walking surface

\*ASTM D226 UL marked felts are the only felts with a class A rating. \*See InterWrap.com/LifetimeWarranty for complete coverage and restrictions

Distributed by:

