

weaving a better world™

FOR IMMEDIATE RELEASE

December 1, 2014 Vancouver, BC Contact: Drew Gagnier - Senior Marketing Manager InterWrap T: 778.945.2884 E: dgagnier@interwrap.com www.interwrap.com

InterWrap announces positive changes to its RhinoRoof[®] roofing underlayment product use and specifications.

Previously RhinoRoof U15 was specified for use under "Asphalt Shingles only". Effective immediately RhinoRoof is now warranted and recommended for usage under; asphalt shingles, metal in residential applications, and cedar shakes.

These recommendations come after 3 years of field testing and analysis by InterWrap's internal R&D department as well as independent testing from Intertek labs. Find below a summary of the positive technical and specification improvements:

- U15 is now recommended for use under: asphalt and synthetic shingles, metal in residential applications, and shakes
- The UV exposure rating for U15 has now been increased from 30 to 60 days
- Steep Slope greater than 7:12 installation restrictions have been removed
- If product is covered within 24 hours it can be anchored with corrosive resistant 3/8"head
- 1" leg roofing nails and use of every other anchoring mark is acceptable
- Going forward RhinoRoof U15 will have the following standards and certifications:
- ASTM D226 Type 1 & II, ASTM 4869, CSA A123.3
- Class 4 Hail rating pending
- FBC & Miami-Dade pending
- ICC / C CR pending
- Product supports a Class A fire rating ASTM E108
- Product has now been certified to contribute to LEED® points
- Limited Warranty has been increased from 10 years to 20 years see web for details

For more information about InterWrap's roofing products, visit www.interwrap.com/roofing

InterWrap is a global leader in the manufacturing and distribution of extrusion coated woven solutions and diverse multilayer laminated reinforced plastic substrates. International manufacturing and distribution facilities located in North America, Europe, Asia and the South Pacific, allow InterWrap the competitive advantage to deliver a coated woven solution better and faster anywhere in the world.