

# RhinoRoof™ Synthetic Roofing Underlayment



## Technical Bulletin

August 28th, 2012

**Subject:** RhinoRoof™ Synthetic Roofing Underlayment installation now includes GREATER than 7/12 roof pitch applications:

Effective immediately the RhinoRoof installation guidelines are modified to read:

- Roof slopes "GREATER" than 7/12 pitch use only Plastic Cap and Nails and covered by primary roofing material within 24 hours.
- Plastic Cap and Nails are defined as a minimum 1" (25mm) diameter plastic or metal cap with either ring shank nails (preferred) or smooth leg nails (acceptable).
- "MUST" anchor each location as printed on product.

We re-state the following good safety precautions:

- Slip resistance may vary with surface conditions from debris that accumulates, weather, footwear and roof pitch.
- Good safety practices should be followed on steep slope roofs, such as use of tie-offs, toe boards, ladders and/or safety ropes and personal body harnesses. Follow OSHA guidelines.

Any questions call your area representative, information available on our Web site: [www.interwrap.com/roofing](http://www.interwrap.com/roofing) or call our Customer Service: 1 888 713 7663.

GARY H SCHINNING  
Division Manager – Roofing Products  
InterWrap Inc.  
202 Mariah Court  
Merritt Island, FL 32953-3053

Tel: 321-452-7919  
Fax: 321-452-7920  
B Cell: 321-578-2777  
Email: [gschinning@interwrap.com](mailto:gschinning@interwrap.com)  
Web: [interwrap.com/roofing](http://interwrap.com/roofing)



weaving a better world™

**Customer Service**  
**Toll Free: 1-888-713-7663**



*Break free from felt!™*